

TRMS 1000A AC/DC clamp meter with Bluetooth connectivity

DCM6500BT



- ☐ Measurements: AC/DC Voltage, AC/DC Current, Frequency, Capacitance, and Resistance
- ☐ Up to 3000A AC (with Flexible AC Current probe)
- ☐ True RMS measurement (TRMS)
- ☐ Diode and continuity test
- ☐ Non-contact voltage detection
- ☐ Automatic range
- ☐ 6000 counts
- ☐ Max/Min/Relative values
- ☐ Bluetooth connectivity
- ☐ Auto-power off
- ☐ Low battery indicator
- ☐ CAT IV conforms EN 61010



DCM6500BT

TRMS 1000A AC/DC clamp meter with Bluetooth connectivity

General	
Display	6000 counts
TRMS measurements	✓
Backlight	✓
Data Hold	✓
Diode and continuity test	✓
Auto-ranging	✓
MIX/MAX/REL values	✓
NCVD (Non-Contact Voltage Detection)	✓
Worklight	✓
Auto power off	✓
Connectivity	Bluetooth
Jaw size	40mm
Dimensions	130x255x60mm (5,11x10,03x2,36")
Weight	765g (26,98oz)
Power Supply	LR03, 3x1,5V AAA
Standards	EC 61010-1, IEC/EN61010-2-033
Safety rating	CAT IV 600V, CAT III 1000V
Accessories included	Test leads, user manual, calibration certificate, Type-K temperature thermocouple, pouch and batteries

DCM6500BT

TRMS 1000A AC/DC clamp meter with Bluetooth connectivity

Specifications	
DC Voltage	60.00mV/600.0mV/6.000V/60.00V/ 600.0V/1000V
AC Voltage	60.00mV/600.0mV/6.000V/60.00V/ 600.0V/750V
AC Current	60.00A/600.0A/1000A
AC Current(FLEX)	300.0A/3000A
DC Current	60.00A/600.0A/1000A
Resistance	600.0Ω/6.000kΩ/60.00kΩ/600.0kΩ/ 6.000MΩ/20.00MΩ
Frecuency	60.00Hz/600.0Hz/6.000kHz/60.00kHz
Duty Cycle	1-99%
Capacitance	60.00nF/600.0nF/6.000μF/60.00μF/ 600.0 μF/6.000Fm
Temperature	-50°C ~ 599.9°C/600°C ~ 760°C -58°F ~ 999.9°F/1000°C ~ 1400°F

Ordering information	
SKU	KPSDCM6500BTCBINT
EAN code	8435394788975
UPC code	810053678619
Pcs/box	30